

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
3 June 2004 (03.06.2004)

PCT

(10) International Publication Number  
**WO 2004/047434 A1**

(51) International Patent Classification<sup>7</sup>: **H04N 5/64**

(74) Agent: **GROENENDAAL, Antonius, W., M.**; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(21) International Application Number:  
PCT/IB2003/004712

(22) International Filing Date: 21 October 2003 (21.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
02079771.8 15 November 2002 (15.11.2002) EP

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **MATTHYS, Erwin, M., A.** [BE/BE]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

Published:

— with international search report

[Continued on next page]

(54) Title: **DEVICE HAVING AT LEAST ONE LOUDSPEAKER AND AT LEAST ONE COIL**



(57) Abstract: In a device having at least one loudspeaker (21) and one coil (15), the influence of a magnetic field being generated by the loudspeaker (21) on a magnetic field being generated by the coil (15) is decreased without enlarging the distance between the loudspeaker (21) and the coil (15). This is achieved by positioning the loudspeaker (21) with respect to the coil (15) such that a central axis (28) of the loudspeaker (21) and windings (17) of the coil (15) which are closest to the loudspeaker (21) extend substantially in the same plane, wherein, in this plane, the central axis (28) of the loudspeaker (21) extends substantially parallel to these closest windings (17). In this arrangement, lines of force (27) of the magnetic field being generated by the loudspeaker (21) do not cross the larger part of the windings (17) of the coil (15).